

C-series

2000 system

OUTDOOR CELL CEILING SYSTEM 室外網格天花系統



DRAGON^{zinc} C2000 External Cell ceiling system applied an open plan ceiling design. It is composed of element A, B, C1 cross runner and C3 main runner. The whole ceiling is suspended by Hanger bracket (C-103) with L-angle frame. Distance between each main runner (C3) is 600mm. Each unit is composed of 600x600mm modules. In addition, the Security clip (C-104) is used to increase the strength of windproofing of the ceiling.

Suspension

The suspension of this system is mainly hanged by Cell ceiling support (C-103) to suspend each main runner in the ceiling (FIG. A). The Runner connector (C-105) is used to connect all runners.


天龍牌 C2000 室外網格天花系統是一種開放式的天花設計，整個天花吊頂主要由A料、B料、C1副龍骨和由間距為600mm的C3主龍骨組合而成；每個小單元由600x 600mm的鋁合金條狀天花組合而成。其吊掛結構主要採用網格專用龍骨吊碼(C-103)固定於角鐵架之底部，懸掛整幅天花。另外，安裝網格防風碼(C-104)進一步提升了整幅天花的防風能力。

吊掛系統

該系統的吊掛結構主要由網格吊掛件(C-103)直接懸掛整幅天花的主龍骨。使用主龍骨駁碼(C-105)連接各主龍骨。

Model No. 型號	Dimension 規格尺寸
C- 50	50 x 50 mm
C- 75	75 x 75 mm
C- 100	100 x 100 mm
C- 150	150 x 150 mm
C- 180	180 x 180 mm
C- 200	200 x 200 mm
C- 300	300 x 300 mm

Model No. 型號	Parts Name 組件名稱
1. A-600	Cell Element 網格組件 (A料)
2. B-600	Cell Element 網格組件 (B料)
3. C1-600	Cross Runner 副龍骨 (C1料)
4. C3-1800	Main Runner 主龍骨 (C3料)
5. CLT	Light Adapter 燈盒
6. C-103	Hanger Bracket 網格龍骨吊碼
7. C-104	Security Clip 網格防風碼
8. A-900	GMS L-angle 電解角鐵
9. C-107	Runner Connector 主龍骨駁碼



Suspension Drawing : 2000 Outdoor Cell Ceiling System
吊掛示意圖：2000 室外網格天花系統

